



- nominal sensing distance $S_n = 1 \text{ mm}$
- supply voltage 10-30 V
- type N.O. PNP
- rated operational current $I_e = 10 \text{ mA}$
- housing diameter M5 x 0.5
- connector M8
- tightening torque max 2 Nm
- electromagnetic compatibility according to EN60947-5-2



NUMERO POSIZIONI / POSITIONS	12
CONI / TAPERS	HSK63
CENTRO CONI / TOOLS CENTER DIAMETER	350
INTERASSE PINZA / TOOLS CENTER DISTANCE	90
MASSA SINGOLO UTENSILE / SINGLE TOOL WEIGHT	6
PESO MASSIMO SUL DISCO /TOTAL WEIGHT MAX	36
MOTORE SCHNEIDER LEXIUM BMH0701P16A2A	
COPPIA NOMINALE / RATED TORQUE	1.3 Nm
COPPIA DI PICCO / MAX TORQUE	4.2 Nm
VELOCITA' NOMINALE MOTORE / MOTOR RATED SPEED	5500 RPM
VELOCITA' MASSIMA MOTORE / MOTOR MAX SPEED	8000 RPM
POTENZA / POWER	0.75 kW
RAPPORTO DI TRASMISSIONE / GEAR RATIO	90
VELOCITA' DISCO DI PROGETTO / DESIGN DISC ROTATION SPEED	25 RPM
POSIZIONE DI LAVORO / WORKING POSITION	VERTICAL

[illegible]