




Prestazioni - Performances



Specifiche tecniche / Technical specifications	
Potenza max. (serv. S1) / Max. Power.(S1 duty)	20 kW @ 10600 Rpm
Coppia max. (serv. S1) / Max. Torque (S1 duty)	17.8 Nm
Corrente (serv. S1) / Current (S1 duty)	48 A
Potenza max. (serv. S6 60%) / Max. Power.(S6 60% duty)	22.3 kW @ 10600 Rpm
Coppia max. (serv. S6 60%) / Max. Torque (S6 60% duty)	20.1 Nm
Corrente (serv. S6 60%) / Current (S6 60% duty)	50 A
Tensione / Voltage	380 V
Motore / Motors	Sincrono / Synchronous
Numero poli / Poles	4
Velocità rotazione max / Max Speed	24 000 Rpm
Rotazione / Rotation	CW - CCW
Azionamento / Supply	con inverter / by inverter
Attacco utensile / Tool interface	HSK 63A
Cuscinetti / Ball bearings	Ceramici obliqui ad alta velocità alta precisione / Ceramic high speed high precision angular contact ball bearings Ant./Front: coppia / pair Post./Rear: coppia / pair
Raffreddamento / cooling	a liquido mediante scambiatore di calore/ liquid by heat exchanger
Sensoristica / Sensors	S1 Afferraggio utensile / Tool lock S2 Pinza aperta / Open clamp S3 Rotazione albero / Spindle rotation
Encoder	SYN/COS 1Vpp 256 impul./giro+imp. rifer. SYN/COS 1Vpp 256 pulse/rev.+ref. mark
Connessioni pneumatiche / Air inlets	Sblocco uten./Release. tool: E6 9.5-10.5 bar Pressur. - air seal. E6 4-4.5 bar Soffio cono/Taper cleaning E6 4-4.5 bar Taper cleaning / air tool E6 4-4.5 bar
Peso / Weight	25 kg